

10/527122

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)


PCT

(10) International Publication Number
WO 2004/023029 A1

- (51) International Patent Classification⁷: **F17C 9/02**
- (21) International Application Number:
PCT/CA2003/001345
- (22) International Filing Date:
3 September 2003 (03.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2,401,926 6 September 2002 (06.09.2002) CA
- (71) Applicant (for all designated States except US): **WEST-PORT RESEARCH INC.** [CA/CA]; 2nd Floor, 1700 West 75th Avenue, Vancouver, British Columbia V6P 6G2 (CA).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): **GRAM, Anker** [CA/CA]; 1280 Arbutus Street, Vancouver, British Columbia V6J 3W6 (CA). **URSAN, Mihai** [CA/CA]; 605 - 4960 Sanders Street, Burnaby, British Columbia V5H 1S9 (CA).
- (74) Agents: **OYEN, Gerald, O., S. et al.**; Oyen Wiggs Green & Mutala, #480 - The Station, 601 West Cordova Street, Vancouver, British Columbia V6B 1G1 (CA).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
— with amended claims
- Date of publication of the amended claims: 27 May 2004

[Continued on next page]

(54) Title: **COMBINED LIQUEFIED GAS AND COMPRESSED GAS RE-FUELING STATION AND METHOD OF OPERATING SAME**



(57) Abstract: A re-fueling station is provided for selectively dispensing fuel in the form of liquefied gas or compressed gas. The re-fueling station comprises a storage tank within which liquefied gas may be stored; a dispensing system comprising: (a) a first dispenser for dispensing compressed gas; (b) a second dispenser for dispensing liquefied gas; (c) a heat exchanger operable to transfer heat to the fuel; (d) a flow diverter operable to receive fuel through an inlet and selectively direct fuel through one of a first outlet or a second outlet; (e) conduits through which fuel may flow from the first outlet to the heat exchanger and then to the first dispenser, or from the second outlet to the second dispenser; and, (f) a positive displacement fuel pump operable to draw fuel from the storage tank and discharge fuel to the inlet of the flow diverter. A method of operating the re-fueling station comprises operating the fuel pump in a low speed mode when fuel is directed to said first dispenser to supply compressed gas and operating the fuel pump in a high speed mode when fuel is directed to the second dispenser to supply liquefied gas.

WO 2004/023029 A1